



Specification

- Uniform and solid core non-combustible calcium sulphate with high-density fibers.
- The top surface of the panel is porcelain tile.
- The edges of the panel are made in self-extinguishing sound minimizing ABS material.
- The panels have an undercut angle of 4°
- The panel dimension is 23.62" x 23.62" (600x600mm)

Elevate™ performance ratings:

- Rolling loads are expressed in pounds per caster, all other data is stated in maximum pounds of load and inches of deflection or permanent set.
- Total System Weight= 14.2 lbs./sq. ft. at 15" FFH. Total Panel Weight= 55 lbs.

Key to performance ratings:

- Global IFS has tested its flooring system to "Recommended Test Procedures for Access Flooring"-Ceiling and Interior Systems Construction Association (CISCA). Uniform and Impact tests have also been conducted. Stringers are edge supporting. Testing reflects weakest point, top surface deflection in accordance with CISCA.
 1. Uniform load data is based on maximum deflection of 0.040". Typical slabs under access floors have uniform load capacities less than the rating of lowest uniform load capacity of any Elevate™ series floor.
 2. Rolling tests used in the CISCA test procedures are performed as follows: 10 passes with a 3" x 1-13/16" caster; 10,000 passes with a 6" x 2" caster. Worst-case permanent set (inches) is shown for each system.
 3. Impact tests are based on 36" drops onto a 1 inch square indenter without ultimate failure of the system.
 4. Concentrated load is applied over a one square inch.

System Loading

System	Concentrated	Rolling 10 Pass	Rolling 10-K Pass	Uniform	Ultimate
Elevate™ RAF	1600 lbs <0.10"	800 lbs	600 lbs	700 psf	1900 psf